



ProGlide


High Performance Sliding Door



High Performance Sliding Door

The ProGlide range from Alspec has been designed with Australia's unique architecture and climate in mind. The door allows architects and designers the freedom to achieve large expansive openings without the need to compromise on performance or aesthetics.

Specifying Alspec's ProGlide range ensures the client receives a solid, durable, high performance product.



Key Features


- High water performance sill options
- Large sliding panels, ideal for housing, apartment and commercial applications
- Inside or outside sliding panels, allowing multiple panel designs
- Allows up to 4 panels stacking in each direction
- Heavy duty interlocks for high wind load requirements
- Accepts up to 13.52mm single glazed and up to 28mm double glazing units, allowing the designer to achieve the most demanding thermal and acoustic specifications
- 90 degree post free corner option
- Heavy duty rollers up to 200kg per panel
- Bevelled rail options
- 28mm slim interlock option also available

Technical Specifications

Frame Dimensions		Acoustic Performance		Thermal Performance	
Option 1	101 x 50mm	Glass Type	Rw (C; C _{tr})	Uw range SG	4.3 - 6.1
Option 2	151.5 x 50mm	6.38mm Laminate	32 (0, -2)	SHGC range SG	0.38 - 0.66
Option 3	202 x 50mm	10.5 Vlam Hush	36 (0, -2)	Uw range DG	2.7 - 3.9
Maximum Product Performance		12.76 Laminate	35 (0, -2)	SHGC range DG	0.22 - 0.55
SLS (Pa)	3000	6/12/9.52mm IGU	39 (-2, -5)	Glazing Details	
ULS (Pa)	6000	6.76/14/6.76mm IGU	38 (-2, -4)	Single Glazed	5 - 13.52mm
Water (Pa)	700	10.38/12/6.38mm IGU	38 (-2, -4)	Double Glazed	18 - 28mm
Maximum Recommended Sizes		Compatible Systems		McArthur Evo Centre Pocket Framing	
Height	3150mm	ecoFRAMEplus Centre Pocket Double Glazed Framing		Hunter Evo Flush Glazed Framing	
Sash Width	2250mm				
Weight	200kg per panel				

Typical Configurations

Double Track



Triple Track

